# INDEX TO
# EXPERIMENTAL MECHANICS
## Volume 24, 1984

## Title Index


Application of the Least-squares Method to Elastic and Photoelastic Calibration of Orthotropic Composites — R. Prabhakaran and R.G. Chermahini, 17-21 (Mar.).

Beam-quality Analysis of Surface Finish by Moiré Deflectometry — I. Glatt, A. Livnat and O. Kafri, 248-251 (Sept.).

Biaxial Stress Transducer for Fabrics, A — R.B. Testa and W. Boctor, 33-39 (Mar.).

Buckling of a Spherical Dome in a Centrifuge — J.H. Prevost, D.P. Billington, R. Rowland and C.C. Lim, 203-207 (Sept.).

Continuous Measurement of Material Damping During Fatigue Tests — P.W. Whaley, P.S. Chen and G.M. Smith, 342-348 (Dec.).

Deformation Measurement During Powder Compaction by a Scanning-moiré Method — Y. Morimoto and T. Hayashi, 112-116 (June).

Delta-element Reusable Strain Transducer, The — T.F. Leahy, 191-202 (Sept.).

Determination of Stress-intensity Factors of Fillet-welded T-Joints by Computer-assisted Photoelasticity — C.L. Tsai and S.K. Park, 233-242 (Sept.).

Determination of the Components of the Strain Tensor in Holographic Interferometry, The — C.A. Sciammarella and R. Narayanan, 257-264 (Dec.).

Development and Calibration of a Dynamic-contact-force Transducer — D. Goldar, V.S. Sethi, O.P. Khurana and S.R. Verma, 187-190 (Sept.).

Development and Characterization of Orthotropic-birefringent Materials — I.M. Daniel, G.M. Koller and T. Niiro, 135-143 (June).

Effects of *R*-Ratio on Crack Initiation at External Discontinuities in Autofrettaged Cylinders — R.R. Fujczak, 122-128 (June).

Experimental Investigation on Isoclinic Parameters in Viscoelastoplastic Materials Under Cyclic Stresses, An — H. Tobushi, Y. Narumi, Y. Ohashi and W. Nakane, 87-92 (June).

Experimental Method for Determining the Dynamic Contact Law, An — J.F. Doyle, 10-16 (Mar.).

Further Developments in Determining the Dynamic Contact Law — J.F. Doyle, 265-270 (Dec.).

Hole-shape Optimization in a Finite Plate in the Presence of Auxiliary Holes — K. Rajaiah and N.K. Naik, 157-161 (June).

Hybrid Experimental-Numerical Stress Analysis — Discussion by K.A. Jacob, 232 (Sept.).

Impact Response of a Circular Membrane — C.L. Farrar, 144-149 (June).

Impact-tension Compression Test by Using a Split-Hopkinson Bar — K. Ogawa, 81-85 (June).

Investigation of Fatigue and Fretting in a Dovetail Joint, An — C. Ruiz, P.H.B. Boddington and K.C. Chen, 208-217 (Sept.).

Iosipescu Shear Test as Applied to Composite Materials, The — Discussion by M. Arcan, 66-67 (Mar.).

Isopachic Contouring of Opaque Plates — D. Post, R. Czarnek and A. Asundi, 169-176 (Sept.).

Loads Between Disks in a System of Discrete Elements — A.J. Durelli and D. Wu, 337-341 (Dec.).

Measurement of Residual Stresses by the Hole-drilling Method: Influences of Transverse Sensitivity of the Gages and Relieved-strain Coefficients — M. Kabiri, 252-256 (Sept.).

Method to Simplify the Strength Design of Bolted Joints—Case of Connecting-rod Bolts, A — M. Hagiwara, 28-32 (Mar.).

Mode III Stress-intensity Factors in Cracked Orthotropic Plates—An Analogy with Propagating Cracks in Isotropic Media — P.S. Theocaris and H.G. Georgiadis, 177-183 (Sept.).

Modified Instrumented Charpy Test for Cement-based Composites, A — V.S. Gopalaratnam, S.P. Shah and R. John, 102-111 (June).

Moiré Interferometry with ±45-deg Gratings — R. Czarnek and D. Post, 68-74 (Mar.).

New Application of the Differential Interferometry for Stress Analysis, A — H. Schwieger, 277-285 (Dec.).

New Method for Measuring Impulsive Force at Contact Parts, A — S. Tanimura, 271-276 (Dec.).

New Technique to Investigate Necking in a Tensile Hopkinson Bar — L.A. Cross, S.J. Bless, A.M. Rajendran, E.A. Strader and D.S. Dawicke, 184-186 (Sept.).

Nondestructive Residual-stress Measurement on the Inside Surface of Stainless-steel Pipe Weldments — C.O. Ruud, P.S. DiMascio and D.M. Meicher, 162-169 (June).

Nonuniform Residual-stress Measurement by Hole-drilling Method — M. Kabiri, 328-336 (Dec.).

Photoelastic-coating Analysis of Dynamic Stress Concentration in Composite Strips — K. Kawata, N. Takeda and S. Hashimoto, 316-327 (Dec.).

Photoelastic Study of Axially Loaded Thick-notched Bars — Discussion by R. Richards, Jr., 85-86 (June).

Photoviscoelastic Analysis of Thermal Stress in a Quenched Epoxy Beam — S. Sugimori, Y. Miyano and T. Kunio, 150-156 (June).

Residual Stresses and Warp Generated by One-sided Quench of an Epoxy-resin Beam — Y. Miyano, M. Shimbo and T. Kunio, 75-80 (Mar.).

Resistance-foil Strain-gage Technology as Applied to Composite Materials — M.E. Tuttle and H.F. Brinson, 54-65 (Mar.).

Resistance Strain Gage Revisited, The — C.C. Perry, 286-299 (Dec.).

Sensitivity of the Fringe-interpretation Technique in Laser Holographic-interferometry Measurements, On the — T.R. Hsu and R. Lewak, 40-43 (Mar.).

Separation of Dynamically Induced Low-frequency Stresses in Rods and Pipes — G. Pavič, 1-9 (Mar.).

Shear Properties and a Stress Analysis Obtained from Vinyl-ester Iosipescu Specimens — J.L. Sullivan, B.G. Kao and H. Van Oene, 223-232 (Sept.).

Strains in Flat Plates from Moiré-displacement Patterns — B.B. Raju, B.S. West and A.J. Piekutowski, 93-101 (June).

Stress Concentration in Machine Components with Complex Shape — H.S. Al-Rubeye, 308-315 (Dec.).

Stresses in a Quasi-isotropic Pin-loaded Connector Using Photoelasticity — M.W. Hyer and D. Liu, 48-53 (Mar.).

Study of Flaw Identification in Adhesive Bonds Using a Technique of Impact Modification, A — V.H. Kenner, G.H. Staab and H.S. Jing, 243-247 (Sept.).

Surface Curvature Analyzed with a Grid-reflection Technique — V.J. Parks, 44-47 (Mar.).

Transient Thermal Stresses in a Strip with an Eccentric Hole — T. Iwaki and K. Miyao, 22-27 (Mar.).

Two-dimensional Fluid-velocity Measurements by Use of Digital-speckle Correlation Techniques — Z.H. He, M.A. Sutton, W.F. Ranson and W.H. Peters, 117-121 (June).

Ultrasonic-shear-wave Measurement of Known Residual Stress in Aluminum — G.V. Blessing, N.N. Hsu and T.M. Proctor, 218-222 (Sept.).

Use of Mixed-mode Stress-intensity Algorithms for Photoelastic Data — C.W. Smith and O. Olaosebikan, 300-307 (Dec.).

Validity of Compliance Calibration to Cracked Concrete Beams in Bending — S.E. Swartz and C.G. Go, 129-134 (June).


## Author Index


**Al-Rubeye, H.S.** — Stress Concentration in Machine Components with Complex Shape, 308-315 (Dec.).

**Arcan, M.** — Discussion of 'The Iosipescu Shear Test as Applied to Composite Materials,' 66-67 (Mar.).

**Asundi, A.** — Isopachic Contouring of Opaque Plates, 169-176 (Sept.).

**Billington, D.P.** — Buckling of a Spherical Dome in a Centrifuge, 203-207 (Sept.).

**Bless, S.J.** — New Technique to Investigate Necking in a Tensile Hopkinson Bar, 184-186 (Sept.).

**Blessing, G.V.** — Ultrasonic-shear-wave Measurement of Known Residual Stress in Aluminum, 218-222 (Sept.).

**Boctor, W.** — A Biaxial Stress Transducer for Fabrics, 33-39 (Mar.).

**Boddington, P.H.B.** — An Investigation of Fatigue and Fretting in a Dovetail Joint, 208-217 (Sept.).

**Brinson, H.F.** — Resistance-foil Strain-gage Technology as Applied to Composite Materials, 54-65 (Mar.).

**Chen, K.C.** — An Investigation of Fatigue and Fretting in a Dovetail Joint, 208-217 (Sept.).

**Chen, P.S.** — Continuous Measurement of Material Damping During Fatigue Tests, 342-348 (Dec.).

**Chermahini, R.G.** — Application of the Least-squares Method to Elastic and Photoelastic Calibration of Orthotropic Composites, 17-21 (Mar.).

**Cross, L.A.** — New Technique to Investigate Necking in a Tensile Hopkinson Bar, 184-186 (Sept.).

**Czarnek, R.** — Moiré Interferometry with ±45-deg Gratings, 68-74 (Mar.).
Isopachic Contouring of Opaque Plates, 169-176 (Sept.).

**Daniel, I.M.** — Development and Characterization of Orthotropic-birefringent Materials, 135-143 (June).

**Dawicke, D.S.** — New Technique to Investigate Necking in a Tensile Hopkinson Bar, 184-186 (Sept.).

**DiMascio, P.S.** — Nondestructive Residual-stress Measurement on the Inside Surface of Stainless-steel Pipe Weldment, 162-169 (June).
**Doyle, J.F.** — An Experimental Method for Determining the Dynamic Contact Law, 10-16 (Mar.).
Further Developments in Determining the Dynamic Contact Law, 265-270 (Dec.).
**Durelli, A.J.** — Loads Between Disks in a System of Discrete Elements, 337-341 (Dec.).
**Farrar, C.L.** — Impact Response of a Circular Membrane, 144-149 (June).
**Fujczak, R.R.** — Effects of *R*-Ratio on Crack Initiation at External Discontinuities in Autofrettaged Cylinders, 122-128 (June).
**Georgiadis, H.G.** — Mode III Stress-intensity Factors in Cracked Orthotropic Plates—An Analogy with Propagating Cracks in Isotropic Media, 177-183 (Sept.).
**Glatt, I.** — Beam-quality Analysis of Surface Finish by Moiré Deflectometry, 248-251 (Sept.).
**Go, C.G.** — Validity of Compliance Calibration to Cracked Concrete Beams in Bending, 129-134 (June).
**Goldar, D.** — Development and Calibration of a Dynamic-contact-force Transducer, 187-190 (Sept.).
**Gopalaratnam, V.S.** — A Modified Instrumented Charpy Test for Cement-based Composites, 102-111 (June).
**Hagiwara, M.** — A Method to Simplify the Strength Design of Bolted Joints—Case of Connecting-rod Bolts, 28-32 (Mar.).
**Hashimoto, S.** — Photoelastic-coating Analysis of Dynamic Stress Concentration in Composite Strips, 316-327 (Dec.).
**Hayashi, T.** — Deformation Measurement During Powder Compaction by a Scanning Moiré Method, 112-116 (June).
**He, Z.H.** — Two-dimensional Fluid-velocity Measurements by Use of Digital-speckle Correlation Technique, 117-121 (June).
**Hsu, N.N.** — Ultrasonic-shear-wave Measurement of Known Residual Stress in Aluminum, 218-222 (Sept.).
**Hsu, T.R.** — On the Sensitivity of the Fringe-interpretation Technique in Laser Holographic-interferometry Measurements, 40-43 (Mar.).
**Hyer, M.W.** — Stresses in a Quasi-isotropic Pin-loaded Connector Using Photoelasticity, 48-53 (Mar.).
**Iwaki, T.** — Transient Thermal Stresses in a Strip with an Eccentric Hole, 22-27 (Mar.).
**Jacob, K.A.** — Discussion of 'Hybrid Experimental–Numerical Stress Analysis,' 232 (Sept.).
**Jing, H.S.** — A Study of Flaw Identification in Adhesive Bonds Using a Technique of Impact Modification, 243-247 (Sept.).
**John, R.** — A Modified Instrumented Charpy Test for Cement-based Composites, 102-111 (June).
**Kabiri, M.** — Measurement of Residual Stresses by the Hole-drilling Method: Influences of Transverse Sensitivity of the Gages and Relieved-strain Coefficients, 252-256 (Sept.).
Nonuniform Residual-stress Measurement by Hole-drilling Method, 328-336 (Dec.).
**Kafri, O.** — Beam-quality Analysis of Surface Finish by Moiré Deflectometry, 248-251 (Sept.).
**Kao, B.G.** — Shear Properties and a Stress Analysis Obtained from Vinyl-ester Iosipescu Specimens, 223-232 (Sept.).
**Kawata, K.** — Photoelastic-coating Analysis of Dynamic Stress Concentration in Composite Strips, 316-327 (Dec.).
**Kenner, V.H.** — A Study of Flaw Identification in Adhesive Bonds Using a Technique of Impact Modification, 243-247 (Sept.).
**Khurana, O.P.** — Development and Calibration of a Dynamic-contact-force Transducer, 187-190 (Sept.).
**Koller, G.M.** — Development and Characterization of Orthotropic-birefringent Materials, 135-143 (June).
**Kunio, T.** — Residual Stresses and Warp Generated by One-sided Quench of an Epoxy-resin Beam, 75-80 (Mar.).
Photoviscoelastic Analysis of Thermal Stress in a Quenched Epoxy Beam, 150-156 (June).
**Leahy, T.F.** — The Delta-element Reusable Strain Transducer, 191-202 (Sept.).
**Lewak, R.** — On the Sensitivity of the Fringe-interpretation Technique in Laser Holographic-interferometry Measurements, 40-43 (Mar.).
**Lim, C.C.** — Buckling of a Spherical Dome in a Centrifuge, 203-207 (Sept.).
**Liu, D.** — Stresses in a Quasi-isotropic Pin-loaded Connector Using Photoelasticity, 48-53 (Mar.).
**Livnat, A.** — Beam-quality Analysis of Surface Finish by Moiré Deflectometry, 248-251 (Sept.).
**Melcher, D.M.** — Nondestructive Residual-stress Measurement on the Inside Surface of Stainless-steel Pipe Weldment, 162-169 (June).
**Miyano, Y.** — Residual Stresses and Warp Generated by One-sided Quench of an Epoxy-resin Beam, 75-80 (Mar.).
Photoviscoelastic Analysis of Thermal Stress in a Quenched Epoxy Beam, 150-156 (June).
**Miyao, K.** — Transient Thermal Stresses in a Strip with an Eccentric Hole, 22-27 (Mar.).
**Morimoto, Y.** — Deformation Measurement During Powder Compaction by a Scanning Moiré Method, 112-116 (June).
**Naik, N.K.** — Hole-shape Optimization in a Finite Plate in the Presence of Auxiliary Holes, 157-161 (June).
**Nakane, W.** — An Experimental Investigation on Isoclinic Parameters in Viscoelastoplastic Materials Under Cyclic Stress, 87-92 (June).
**Narayanan, R.** — The Determination of the Components of the Strain Tensor in Holographic Interferometry, 257-264 (Dec.).
**Narumi, Y.** — An Experimental Investigation on Isoclinic Parameters in Viscoelastoplastic Materials Under Cyclic Stresses, 87-92 (June).
**Niiro, T.** — Development and Characterization of Orthotropic-birefringent Materials, 135-143 (June).
**Ogawa, K.** — Impact-tension Compression Test by Using a Split-Hopkinson Bar, 81-85 (June).
**Ohashi, Y.** — An Experimental Investigation on Isoclinic Parameters in Viscoelastoplastic Materials Under Cyclic Stresses, 87-92 (June).
**Olaosebikan, O.** — Use of Mixed-mode Stress-intensity Algorithms for Photoelastic Data, 300-307 (Dec.).
**Park, S.K.** — Determination of Stress-intensity Factors of Fillet-welded T-Joints by Computer-assisted Photoelasticity, 233-242 (Sept.).
**Parks, V.J.** — Surface Curvature Analyzed with a Grid-reflection Technique, 44-47 (Mar).
**Pavić, G.** — Separation of Dynamically Induced Low-frequency Stresses in Rods and Pipes, 1-9 (Mar.).
**Perry, C.C.** — The Resistance Strain Gage Revisited, 286-299 (Dec.).
**Peters, W.H.** — Two-dimensional Fluid-velocity Measurements by Use of Digital-speckle Correlation Techniques, 117-121 (June).
**Piekutowski, A.L.** — Strains in Flat Plates from Moiré-displacement Patterns, 93-101 (June).
**Post, D.** — Moiré Interferometry with ±45-deg Gratings, 68-74 (Mar.).
Isopachic Contouring of Opaque Plates, 169-176 (Sept.).
**Prabhakaran, R.** — Application of the Least-squares Method to Elastic and Photoelastic Calibration of Orthotropic Composites, 17-21 (Mar.).
**Prevost, J.H.** — Buckling of a Spherical Dome in a Centrifuge, 203-207 (Sept.).
**Proctor, T.M.** — Ultrasonic-shear-wave Measurement of Known Residual Stress in Aluminum, 218-222 (Sept.).
**Rajaiah, K.** — Hole-shape Optimization in a Finite Plate in the Presence of Auxiliary Holes, 157-161 (June).
**Rajendran, A.M.** — New Technique to Investigate Necking in a Tensile Hopkinson Bar, 184-186 (Sept.).
**Raju, B.B.** — Strains in Flat Plates from Moiré-displacement Patterns, 93-101 (June).
**Ranson, W.F.** — Two-dimensional Fluid-velocity Measurements by Use of Digital-speckle Correlation Techniques, 117-121 (June).
**Richards, Jr., R.** — Discussion of 'Photoelastic Study of Axially Loaded Thick-notched Bars,' 85-86 (June).
**Rowland, R.** — Buckling of a Spherical Dome in a Centrifuge, 203-207 (Sept.).
**Ruud, C.O.** — Nondestructive Residual-stress Measurement on the Inside Surface of Stainless-steel Pipe Weldments, 162-169 (June).
**Ruiz, C.** — An Investigation of Fatigue and Fretting in a Dovetail Joint, 208-217 (Sept.).
**Schwieger, H.** — A New Application of the Differential Interferometry for Stress Analysis, 277-285 (Dec.).
**Sciammarella, C.A.** — The Determination of the Components of the Strain Tensor in Holographic Interferometry, 257-264 (Dec.).
**Sethi, V.S.** — Development and Calibration of a Dynamic-contact-force Transducer, 187-190 (Sept.).
**Shah, S.P.** — A Modified Instrumented Charpy Test for Cement-based Composites, 102-111 (June).
**Shimbo, M.** — Residual Stresses and Warp Generated by One-sided Quench of an Epoxy-resin Beam, 75-80 (Mar.).
**Smith, C.W.** — Use of Mixed-mode Sress-intensity Algorithms for Photoelastic Data, 300-307 (Dec.).
**Smith, G.M.** — Continuous Measurement of Material Damping During Fatigue Tests, 342-348 (Dec.).
**Staab, G.H.** — A Study of Flaw Identification in Adhesive Bonds Using a Technique of Impact Modification, 243-247 (Sept.).
**Strader, E.A.** — New Technique to Investigate Necking in a Tensile Hopkinson Bar, 184-186 (Sept.).
**Sugimori, S.** — Photoviscoelastic Analysis of Thermal Stress in a Quenched Epoxy Beam, 150-156 (June).
**Sullivan, J.L.** — Shear Properties and a Stress Analysis Obtained from Vinyl-ester Iosipescu Specimens, 223-232 (Sept.).
**Sutton, M.A.** — Two-dimensional Fluid-velocity Measurements by Use of Digital-speckle Correlation Techniques, 117-121 (June).
**Swartz, S.E.** — Validity of Compliance Calibration to Cracked Concrete Beams in Bending, 129-134 (June).
**Takeda, N.** — Photoelastic-coating Analysis of Dynamic Stress Concentration in Composite Strips, 316-327 (Dec.).
**Tanimura, S.** — A New Method for Measuring Impulsive Force at Contact Parts, 271-276 (Dec.).
**Testa, R.B.** — A Biaxial Stress Transducer for Fabrics, 33-39 (Mar.).
**Theocaris, P.S.** — Mode III Stress-intensity Factors in Cracked Orthotropic Plates: An Analogy with Propagating Cracks in Isotropic Media, 177-183 (Sept.).
**Tobushi, H.** — An Experimental Investigation on Isoclinic Parameters in Viscoelastoplastic Materials Under Cyclic Stresses, 87-92 (June).
**Tsai, C.L.** — Determination of Stress-intensity Factors of Fillet-welded T-Joints by Computer-assisted Photoelasticity, 233-242 (Sept.).
**Tuttle, M.E.** — Resistance-foil Strain-gage Technology as Applied to Composite Materials, 54-65 (Mar.).
**Van Oene, H.** — Shear Properties and a Stress Analysis Obtained from Vinyl-ester Iosipescu Specimens, 223-232 (Sept.).
**Verma, S.R.** — Development and Calibration of a Dynamic-contact-force Transducer, 187-190 (Sept.).
**West, B.S.** — Strains in Flat Plates from Moiré-displacement Patterns, 93-101 (June).
**Whaley, P.W.** — Continuous Measurement of Material Damping During Fatigue Tests, 342-348 (Dec.).
**Wu, D.** — Loads Between Disks in a System of Discrete Elements, 337-341 (Dec.).